

<u>ITEM</u> <u>MATERIALS</u>

- (1) BRASS SERVICE SADDLE, CC/ TAPERED THREAD OUTLET.
- (2) BRASS CORPORATION STOP, CC THREAD X COMPRESSION COUPLING.
- (3) COPPER TUBING, TYPE "K" W/ P.E. WRAP.
- (4) TYPE 316 STAINLESS STEEL SADDLE BOLT AND NUTS.

NOTES:

- 1. ALL HOT TAPS SHALL BE PERFORMED PER OWD SPEC. SECTION 306-8.8.4.
- 2. ALL SERVICE TAPS 2-INCHES AND SMALLER SHALL BE INSTALLED WITH A SERVICE SADDLE PER OWD SPEC. SECTION 212-10.3.3.
- 3. ALL SERVICE SADDLES FOR DIP SHALL BE BRASS, DOUBLE STRAP, CC THREAD AS MANUFACTURED BY FORD, JONES, MUELLER, OR APPROVED EQUAL.
- 4. ALL SERVICE SADDLES FOR PVC C900 SHALL BE BRASS, DOUBLE STAINLESS STEEL BAND TYPE, CC THREAD AS MANUFACTURED BY FORD, SMITH—BLAIR, AY MCDONALD, OR APPROVED EQUAL.
- 5. NON-ACTIVE WATER MAINS NEWLY INSTALLED BY DEVELOPER: 2" AND SMALLER SERVICE TAPS MAY BE INSTALLED UNDER CITY WATER INSPECTOR PER WATER DIVISION APPROVED PLANS AND THE WATER DIVISION STANDARD PLANS AND SPECIFICATIONS.
- 6. SADDLE NUTS SHALL BE FINISHED WITH TRIPAC 2000 BLUE COATING SYSTEM OR APPROVED EQUAL.

four Jion 1/31/2023 CITY WATER MANAGER	CITY OF ORANGE WATER DIVISION STANDARDS	OWD STD. DWG.
CITY ENGINEER	SERVICE TAP INSTALLATION	OWD-201
1/31/2023 PUBLIC WORKS DIRECTOR	(COPPER TUBING)	SHEET 1 OF 1