Orange Police Non-Residential Requirements

The City of Orange Municipal Code section 15.52 requires that all building within the city meet specific security standards (Ordinance # 6-22). The following items shall be required on any new or remodeled commercial building/tenant space.

Strike plate – 16 gauge Screws– 3" in wood framed jambs Aluminum jamb reinforced

Non-removable hinge pins (NRP) on out swinging doors

Operable windows/sliding doors shall have passed C.M.B.S.O. forced entry test

Exterior doors – 16 gauge hollow metal or solid core wood

Exterior door hardware shall come from current City of Orange Approved Products List

One motion lever hardware, deadbolt function required on all exterior doors (unless panic $\underline{\text{required}})$

Solid steel cylinder guard/approved escutcheon required

Exterior pair of doors require automatic 5/8" metal flush bolts at head & threshold

Double doors with panic hardware require full length astragal approved by the police department

Office suite doors in multi-occupancy/tenant building to be secured as exterior doors (i.e.-deadbolt)

Skylights shall be protected by rated burglary/impact glazing, or approved burglar bars

HVAC or air duct/vent require burglar bars/screen on any opening exceeding 96 square inches [Iron bars at least ½ in round or 1 in flat steel material spaced no more than 5 inches apart & securely fastened] Building address numbers shall be illuminated, contrast and between 8 and 12 inches in height

Lighting at exterior doorways shall be maintained minimum 1 fc. at ground with vandal proof lenses Lighting on parking & access areas shall be maintained minimum 1 fc. at ground with vandal proof lenses

ANY EXTERIOR CHANGES TO EXISTING BUILDING T.I.'S MUST MEET SECURITY ORDINANCE REQIREMENTS

CRIME PREVENTION BUREAU (714)-744-7327 or (714) 744-7555